One AP 36-0-6

SPREADER SETTINGS

Spreader settings vary by make and model of spreader. It is recommended that individual spreaders are calibrated for the specific product that is to be applied. A walking speed of 3 miles per hour is recommended.

Recommended Approximate
Spreader Settings for One AP 36-0-6
(wheel to wheel overlap)

Northern Blend	Commercial	Residential Irrigated Commercial	
Transition Blend		Commercial	Residential Irrigated Commercial
Spreader	5.5lb product/1000 sq ft	7lb product/1000 sq ft	8.3lb product/1000 sq ft
Turfco T3000	6	6.5	7.5
Cyclone/Spyker	4.75	5	5.5
Lesco #	17	19	20
Lesco letter	G	Н	H 1/2
Vicon 4.5 mph	32	38	40
Lely 4.5 mph	5.25	6	6.5
Perma-Green Mag	25	Fully Open	Fully Open (aggressive overlap)
Andersons AccuPro 2000	M 3/4	0 1/2	Q
Scotts R-8	L 1/2	N 1/2	P 1/2

APPLICATION PRECAUTIONS:

- Keep away from pools, ponds, etc. Do not contaminate potable water.
- Avoid application in high wind conditions to prevent drift and uneven distribution of fertilizer.
- Do not apply with drop-type spreader.
- Many plant nutrients can cause staining of sidewalks. Sweep walkways prior to irrigation. Walkways should be dry at time of application.

Approximate Spread pattern when applying at 7 lbs per 1,000 sq. ft. (2.5LB N/1000) 250-300 particles per square foot

